



Paradigm Flow Services

Howe Moss Drive | Kirkhill Industrial Estate, Dyce | Aberdeen AB21 0GL | United Kingdom



AGENDA



- Flow Assurance Challenges
- Paradigm Remediation Technologies
- Operational Case Studies



FLOW ASSURANCE CHALLENGES

- Lack of maintenance and pigging regimes in pipeline systems can create reduced flow or in worst cases, full-bore blockages caused by wax, sands or hydrates.
- Lines may not have pigging facilities installed.
- Blockage locations and compositions are often unclear.
- Distant blockages can prevent effective chemical circulation.
- Water ingress or chemical incompatibility can cause problems with control umbilical systems.
- Topsides infrastructure is complex with limited space and access.
- Vessel-based campaigns are slow to organize and require multiple vendors, increasing downtime.



REMEDICATION SERVICES



Paradigm's **Pipe-Pulse®** removes flowline and umbilical blockages using a highly controlled hydro-hammer force for breaking down debris.

Pipe-Pulse® is a non-intrusive method of removing blockages including stuck pigs and production residues.



Paradigm's **Flexi-Coil®** is a composite neutrally buoyant flexible pipe that is injected from a small equipment footprint into a pressurised blocked pipe/flow-line capable of reaching extensive distances and navigate over 1,000 degrees of bends.

The Flexi-Coil® system can operate whilst the pipeline remains in production and incorporates technology to remove the blockage by way of concentrated hydraulic force whilst propelling the pipe significant distance.




PIPE-PULSE




- Non-invasive technology
- Controlled pressure pulses, generating an impulse force at the blockage
- Small footprint, quick to mobilise equipment
- Optimal in high-pressure systems over long distances

PARADIGM



CASE STUDY - UK

- Facility – Beryl Alpha, UK North Sea
- Overview – Blocked 1/2" scale inhibitor core within production umbilical.
- Challenge – Length and blockage type unknown.
- Solution – Find Block & Location by volume to locate blockage.
- Pressure Cycling / Pressure Pulsing and locking in at MAOP and monitoring. Blockage located 76m from TUTU.
- On communication of blockage removal, a 1.5-line volume flush at maximum achievable flow rate using MEG was completed.
- Result – Successfully cleared umbilical core returning to normal corrosion inhibitor operations.



FLEXI-COIL



Restore & increase production by removing flow assurance challenges via riser intervention



Enhance production via in-riser gas lift or velocity string technology



No vessel or subsea intervention requirement




Compact design, minimal deck space requirements and suitable for air freight



PARADIGM



Item Description	Gross Weight Kg	Dimensions
Spooler Frame	7,906	3.81m x 2,44m x 2,62m
Power Pack	8,000	3.2m x 2.39m x 2.11m
Drum Spool c/w 7000ft Flexi-Coil®	6,564	3.2m x 3.2m x 2.18m
Control Panel	1,661	2.79m x 1.37m x 2.44m
Injector	2,092	2.13m x 1.63m x 1.77m
BOP	1,136	1.63m x 1.5m 1.44m
Stripper	804	2.39m x 1.22m x 1.32m



Personnel	Quantity	Working Duration
Supervisor	2	24 Hour Operations
Technician	4	24 Hour Operations

FLEXIBILITY IN DEPLOYMENT

- Adaptable surface layout
- Direct Vertical Access (DVA) to riser not required
- Line of sight to riser not required



CASE STUDY: 12" EXPORT PIPELINE – G.O.M.

Challenge

- A full-bore paraffin wax blockage on a main export pipeline in 147 MWD
- Blockage confirmed to be at 1,058m into a 36km pipeline, with the total length being unknown

Solution

- Flexi-Coil® deployed to target paraffin wax blockage via high-pressure liquid jetting using water/solvent mix.
- Flexi-Coil® navigated >810° of system bends

Result

- Blockage successfully remediated and production reinstated to service in <3 weeks
- Communication with the receiving facility was established at ~2km into the pipeline (>950m blockage)
- Over 45 cuttings boxes filled with paraffin wax were removed from the system (~255 tons)
- Zero subsea intervention was required





CASE STUDY : 24" DEAD LEG DECOMMISSIONING

Challenge

- A UK SNS Operator needed to flush an export pipeline which was connected to a producing trunkline system from Cygnus A to the onshore Bacton Terminal
- The line contained a wye-manifold with two closed valves against the producing system, creating a dead leg with an estimated 150m³ of condensate


Solution

- Flexi-Coil[®] was deployed from topsides >1km through 330° of cumulative bends using treated seawater to flush the contents back to topsides and then routed to a disposal well

Result

- Operations to flush the line were completed in < 3 days achieving a cleanliness level of < 30ppm allowing the line to be disconnected
- All operations were completed from the topsides, with zero subsea intervention or environmental impact

PARADIGM



CASE STUDY : 24" DEAD LEG DECOMMISSIONING




Flexi-Coil® Equipment Setup for Operations



Pipeline Status Post Operations

PARADIGM



THANK YOU

