


TGS CCS Baseline and 4D Monitoring tools





#### **Legal Notice**

All data examples, processes, hardcopy digital materials and other intellectual property presented in the attached PowerPoint document(s) constitute valuable and highly confidential trade secrets that are not generally available and are the sole property and proprietary information of TGS or another owner for who TGS acts as an agent.


All information and materials are for internal use only. The sharing, copying or distribution of any of the information provided by TGS to **any third party** is strictly prohibited.

All material included in this presentation was prepared in accordance with accepted practices of the geophysical profession, however, TGS makes no representation or warranty, express or implied, of any kind, including merchantability, quality or reliability of the material or its fitness for any particular purpose. TGS assumes no liability for reliance of anyone on these materials to make any kind of decision. Any action made based on these materials shall be taken at your own risk and expense.


## TGS CCS Baseline and 4D Monitoring tools












# Northern Endurance CCS Development Survey 2022 Northern Endurance Partnership, operated by BP






"Figure 1 Two-way time sections through Endurance comparing 2022 3DHR full-stack reflectivity data (left) compared to the legacy 3D dataset previously used for site characterization (left, reprocessed 2013 TGS Ravenspurn acquisitions, data shown courtesy of TGS)."





#### Poseidon CCS Survey North Sea 2023 (Aker BP, OMV)



Streamer spread: 14 x 50 m x 6000 m

Wide-tow quad source: 87.5 m source separation


Acquisition bin size: 6.25 m x 6.25 m



### Sleipner CCS Pilot - Combining XHR with OBN




- XHR UHR3D Proof of concept
  - Deep tow 10m (gun at 5m)
  - 12 cables (bin size 1.56 x 3.125m)
  - 47 Drop & Pop Nodes was deployed and retrieved cost-efficiently using TGS' new self-recovery system
- Focus on CCS
  - Acquired 3D dataset over existing CCS plume
  - Parameter optimization (Source volume & SP distance)
  - Acquire 4D Repeatability test (5 sail line repeat)
  - Recorded the XHR shots on the sparse nodes for FWI velocity
  - Compare data to conventional datasets






• Drop & Pop
















# Comparisons















2.5km



# Picking on INVERTED FWI velocities









**PROS:** Seamless data quality, time & cost savings & less CO<sub>2</sub> footprint

